

**MASSACHUSETTS INSTITUTE OF TECHNOLOGY
LINCOLN LABORATORY**

**DARPA/TTO PROGRAM
IR BINARY OPTICS**

**SEMIANNUAL TECHNICAL SUMMARY REPORT
TO THE
DEFENSE ADVANCED RESEARCH PROJECTS AGENCY**

1 JULY — 31 DECEMBER 1985

ISSUED 27 FEBRUARY 1986

Distribution limited to U.S. Government agencies and their contractors; critical technology; 25 February 1986. Other requests for this document must be referred to DARPA/TIO, 1400 Wilson Boulevard, Arlington, VA 22209.

WARNING

INFORMATION SUBJECT TO EXPORT CONTROL LAWS

This document may contain information subject to the International Traffic in Arms Regulation (ITAR) or the Export Administration Regulation (EAR) of 1979 which may not be exported, released, or disclosed to foreign nationals inside or outside the United States without first obtaining an export license. A violation of the ITAR or EAR may be subject to a penalty of up to 10 years imprisonment and a fine of \$100,000 under 22 U.S.C. 2778 or Section 2410 of the Export Administration Act of 1979. Include this notice with any reproduced portion of this document.

LEXINGTON

MASSACHUSETTS

95F1206
#787

ABSTRACT

This report describes the work performed at Lincoln Laboratory on IR Binary Optics under the sponsorship of DARPA/TTO during the period 1 July through 31 December 1985.

Accession For	
NTIS CRA&I	<input type="checkbox"/>
DTIC TAB	<input checked="" type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
C-2	57 KC

LIST OF ILLUSTRATIONS

Figure No.		Page
1	Diffractive and Refractive Optics Technologies	3
2	Far Field Sum of Six Coherently Added GaAs Lasers	4
3	Dual Electron Beam — Grating Laser Configuration	5

3. BINARY LASER TELESCOPE

A six-inch primary CO₂ laser telescope, with a 5° aberration corrected FOV, is one of our main research efforts. The technology acquired in this effort could be applied to large space based segmented planar optical apertures and could be used to develop an appropriate embossing technology.

A prototype telescope that can replace the current diamond turned Ritchey-Chretien telescope in our laser radar test bed is under design. In a previous report, we discussed how we placed a lens transfer function on a spatial frequency carrier in the evanescent EM domain. We tested these diffractive lenses and measured diffraction efficiencies as high as 97 percent. The drawback of this approach, however, is the strong efficiency dependence on polarization. Most laser radars, use linearly polarized sources but generate circularly polarized light in the monostatic transmitter. Multilevel binary structures such as shown in Figure 1 can, with only three levels, achieve a diffraction efficiency as high as 90 percent in both polarizations. Therefore, we are now concentrating our efforts on multilevel structures for both laser radar and broadband telescope applications.

4. DIFFRACTIVE WIDEBAND TELESCOPES

Wideband light-weight diffractive infrared telescopes have many applications in FLIR imaging and throw-away optical systems. In order to operate efficiently over a large (>10 percent) bandwidth and with low aberrations, one must operate close to the optical axis. The high spatial frequency carrier approach that sustained near perfect diffraction efficiency in laser telescopes is not feasible here. Our approach has been to build asymmetry into the binary structures by using a multimask approach. With two masks (3 levels) 90 percent diffraction efficiency is feasible. With asymmetric relief profiles, close on-axis planar telescopes and frequency bandwidths in excess of 10 percent appear feasible. Two different mask designs are being tested, one three-level on-axis planar lens, and one three-level off-axis design.

We are designing the telescopes and the appropriate relief structures in collaboration with the University of Rochester and the University of Virginia. Professor Morris of Rochester and his PhD student are calculating the layout and feasible aberration corrections.

5. MODULAR LASER SOURCES

During the past six months we tested the coherent beam addition concept on modular infrared HeNe lasers and on linear arrays of monolithic GaAs lasers. The far-field pattern of the coherent sum (see Figure 2) is virtually indistinguishable from a single laser element, and no far-field sidelobes are generated in the summing process. We are studying cavity feedback and phase locking mechanisms that make coherent addition such a stable process. During FY86 we will test coherent addition on custom designed uncoupled GaAs laser arrays and optimize external cavity designs for maximum laser power output.




Figure 2. Far field sum of six coherently added GaAs lasers.

6. ELECTRON-GRATING LASERS

In September 1985 we set up a laboratory and started a research effort to study the interactions of electron beams with metallic gratings to generate tunable coherent light (see Figure 3). Tunable coherent light can be generated by exploiting the Salisbury effect (i.e., when an electron interacts with a conducting grating at a slant angle), by chirping the grating with a rate equal to the electron's Bremsstrahlung rate, and by placing the grating structure inside a laser cavity. We have already observed tunable incoherent infrared radiation with harmonics throughout the visible spectrum from 2400 lines/mm gratings and 40 KeV electrons. With an optical cavity we will provide feedback to bunch electrons and to generate frequency coherence. We are also upgrading the system to higher e-beam power levels and to improved vacuum levels ($>10^{-8}$ Torr). The new system will be installed in February 1986.

Continued research on electron-grating lasers will establish the feasibility of one-octave tunable frequency lasers in the visible and the infrared. Sources like these will have applications in laser radars, jammers, and other optical systems.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER FSD-TR-85-321	2. GOVT ACCESSION NO. AD 548 578	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) DARPA/TTO Program IR Binary Optics		5. TYPE OF REPORT & PERIOD COVERED Semiannual Technical Summary 1 July - 31 December 1985
7. AUTHOR(s) Wilfrid B. Veldkamp		6. PERFORMING ORG. REPORT NUMBER
8. PERFORMING ORGANIZATION NAME AND ADDRESS Lincoln Laboratory, M.I.T. P.O. Box 73 Lexington, MA 02173-0073		9. CONTRACT OR GRANT NUMBER(s) F19628-85-C-0002
11. CONTROLLING OFFICE NAME AND ADDRESS Defense Advanced Research Projects Agency 1400 Wilson Boulevard Arlington, VA 22209		10. PROGRAM ELEMENT PROJECT TASK AREA & WORK UNIT NUMBERS ARPA Order 4654 Program Element No. 63222E
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Electronic Systems Division Hanscom AFB, MA 01731		12. REPORT DATE 31 December 1985
		13. NUMBER OF PAGES 10
		15. SECURITY CLASS. (of this Report) Unclassified
		16. DECLASSIFICATION AND DOWNGRADING SCHEDULE
18. DISTRIBUTION STATEMENT (of this Report) Distribution limited to U.S. Government agencies and their contractors; critical technology; 25 February 1986. Other requests for this document shall be referred to DARPA/TTO, 1400 Wilson Blvd., Arlington, VA 22209.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
19. SUPPLEMENTARY NOTES		
20. KEY WORDS (Continue on reverse side if necessary and identify by block number) <div style="display: flex; justify-content: space-between;"> <div> binary optics diffraction gratings holographic gratings </div> <div> laser radars coherent beam additions </div> </div>		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) <p>This report describes the work performed at Lincoln Laboratory on IR Binary Optics under the sponsorship of DARPA/TTO during the period 1 July through 31 December 1985.</p>		